


Teil 3 = Taper-Klemmbuchse 2012, Passfedernute n. DIN 6885 Bl.1  
 part 3 = Taper clamping bush 2012, Keyway acc. to DIN 6885 sheet 1

Massenträgheitsmoment / Mass moment of inertia

$$J_{ges.} = 0.014862 \text{ kgm}^2$$

Schraubenanzugsmoment Teil 3- 7/16'' BSW ,  $T_A = 31 \text{ Nm}$

screw tightening torque part 3- 7/16'' BSW ,  $T_A = 31 \text{ Nm}$

Oberflächengüte nach DIN ISO 1302 Reihe 2 Surface quality acc. to DIN ISO 1302 line 2		Schutzvermerk ISO 16016 beachten Note protection mark acc. to ISO 16016			
Allgemeintoleranzen nach DIN ISO 2768 - mH General tolerances acc. to DIN ISO 2768-		Masstab Scale	13:20	Format DIN Size	A3
<b>ROTEX 65 TB1/1 Taper-Klemm Standard</b>			 <b>KTR-Kupplungstechnik GmbH</b> D-48407 Rheine		
gezeichnet drawn	Werkstoff Material	Teilnummer Part number	Kz	Lfd.-Nr. Current number	Index Change
Datum 15.09.04	DIN		M	422542	0
Name KO	Gewicht Weight	5.956			